

Photovoltaic support structure mode

What are the dynamic characteristics of photovoltaic support systems?

Key findings are as follows. Dynamic characteristics of tracking photovoltaic support systems obtained through field modal testing at various inclinations, revealing three torsional modes within the 2.9-5.0 Hz frequency range, accompanied by relatively small modal damping ratios ranging from 1.07 % to 2.99 %.

What is a new cable-supported photovoltaic system?

A new cable-supported photovoltaic system is proposed. Long span, light weight, strong load capacity, and adaptability to complex terrains. The nonlinear stiffness of the new cable-supported photovoltaic system is revealed. The failure mode of the new structure is discussed in detail.

What are the dynamic characteristics of the tracking photovoltaic support system?

Through processing and analyzing the measured modal data of the tracking photovoltaic support system with Donghua software, the dynamic characteristic parameters of the tracking photovoltaic support system could be obtained, including frequencies, vibration modes and damping ratio.

How stiff is a tracking photovoltaic support system?

Because the support structure of the tracking photovoltaic support system has a long extension length and the components are D-shaped hollow steel pipes, the overall stiffness of the structure was found to be low, and the first three natural frequencies were between 2.934 and 4.921.

Does tracking photovoltaic support system have a modal analysis?

While significant progress has been made by scholars in the exploration of wind pressure distribution, pulsation characteristics, and dynamic response of tracking photovoltaic support system, there is a notable gap in the literature when it comes to modal analysis of tracking photovoltaic support system.

What is a flexible PV support structure?

The baseline, unreinforced flexible PV support structure is designated as F. The first reinforcement strategy involves increasing the diameter of the prestressed cables to 17.8 mm and 21.6 mm, respectively. These configurations are named F1-1 and F1-2 for ease of comparison.



Contact us for free full report

Web: https://www.publishers-right.eu/contact-us/ Email: energystorage2000@gmail.com WhatsApp: 8613816583346

